

Listing of Claims:

This listing of claims reflects all claim amendments and replaces all prior versions, and listings, of claims in the application. Material to be inserted is in **bold and underline**, and material to be deleted is in ~~strikeout~~ or (if the deletion is of five or fewer consecutive characters or would be difficult to see) in double brackets [[]].

Please cancel claims 1-4, without prejudice.

Please add new claim 5, as indicated below.

1-4. (Cancelled)

5. (New) A shockproof microphone support device comprising:

a supporting base, composed of a first grip plate and a second grip plate each adapted to be securely connected to a retaining base, wherein each grip plate has:

a top portion, a bottom portion, an upright portion extending between the top and the bottom portion, wherein a plurality of blocks is respectively formed on a side wall of the upright portion of the first grip plate and the second grip plate, a plurality of pin holes is defined at a side wall of the top and bottom portions of the first grip plate, and a plurality of pins is defined at a side wall of the top and bottom

portions of the second grip plate to correspond to the plurality of pin holes;

an ear plate downwardly extending from a flange of the bottom portion; and

a U-like cross-section channel defined by the top portion, the bottom portion and the upright portion, so that when the first grip plate and the second grip plate are securely connected to the retaining base, the two U-like cross section channels of the first and second grip plates define a passage;

a shockproof strip received in the passage and adapted to support a microphone thereon, wherein the shockproof strip is made of a flexible material and further has:

a plurality of dents formed thereon to absorb vibration; and

a plurality of notches is defined in opposed edges of the shockproof strip, whereby after the shockproof strip is received in the passage, the plurality of blocks of the first grip plate and the second grip plate is respectively received in the plurality of notches of the shockproof strip so as to secure the shockproof strip relative to the first grip plate and the second grip plate.